LEAD FREE はんだ付け用 **RoHS Compliant** ペースト

No.FS120-02

HAKOPASTE

容量 60g

●板金加工に ●ホビー全般に ●ステンドグラスに

はんだのなじみが大幅に向上 鉛フリーはんだにも対応

[使用方法]

1. はんだ付けする部分 に適量のペーストを 塗布します。



2 はんだ付けする部分 にこてを当て、はんだ を送ります。



[洗浄方法]

はんだ付け後、残ったペーストをウエス、ティッ シュペーパーなどできれいに拭いとり、さらに きれいなウエス、ティッシュペーパーに IPA(イ ソプロピルアルコール)をしみ込ませて洗浄し ます。

- ※1このペーストは腐食性があるので、 洗浄することをおすすめします。
- ※2 本品をプリント基板などの電気関係 のはんだ付けに使用しないでください。

危険





[危険有害性情報]

- 飲み込むと有害
- 重篤な皮膚の薬傷及び眼の損傷
- 呼吸器の障害のおそれ。
- 長期にわたる又は反復ばく露に よる全身毒性の障害のおそれ
- 長期継続的影響によって 水牛牛物に毒件

◆ペーストではんだ付け可能な金属

銅	真鍮	ブリキ	トタン	アルミ	ステンレス
0	0	0	0	×	×

[安全対策]

- 粉じん/煙/ガス/ミスト/蒸気/ スプレーを吸入しないこと。
- 取扱い後は手をよく洗うこと。
- 保護手袋/保護衣/保護眼鏡/ 保護面を着用すること。

[広急処置]

● 飲み込んだ場合

口をすすぐこと。

無理に叶かせないこと。

● 皮膚(又は髪)に付着した場合

直ちに汚染された衣類を全て脱ぐこと。 皮膚を水(又はシャワー)で洗うこと。

● 眼に入った場合

水で数分間注意深く洗うこと。 次にコンタクトレンズを着用していて 容易に外せる場合は外すこと。

その後も洗浄を続けること。

直ちに医師に連絡すること。



�HAK≪D

白光株式会社

https://www.hakko.com

〒556-0024 大阪市浪速区塩草2丁目4番5号 TEL: (06) 6561-1574 (ft) FAX: (06) 6568-0821

© 2010-2024 HAKKO Corporation, All Rights Reserved.

[保 管]

直射日光の当たらない涼しい場所で 保管すること。

「庭 垂]

内容物、容器は国又は都道府県の規 則に従って廃棄すること。

[使用上の注意]

詳細については SDS を参照するこ と。



For soldering **PASTE**

LEAD FREE RoHS Compliant No.FS120-02

HAKCOPAST

For sheet metal, hobby and stained glass iron

Amount 60g

Improve solder wettability drastically. To comply with lead-Free

■OPERATION

1. Apply appropriate amount of paste on the parts to be soldered.



2. Put the soldering iron on the parts to be soldered and feed the solder.y



■HOW TO CLEAN

After soldering, wipe the remaining flux cleanly such as by using waste cloth or tissue paper.

Then, wet the clean waste cloth or tissue paper with Isopropyl alcohol for additional cleaning.

- *1 It is suggested to clean off the flux residue because the paste has corrosive properties.
- *2 Please do not use this item to solder related to the electricity such as printed wiring boards.

◆Solderable metal

Copper Brass Tin steel Zinc steel | Aluminum | Stainless steel X

DANGER





■ Hazard Statements

- Harmful if swallowed.
- Causes serious skin burns and eve damage.
- May cause damage to respiratory
- May cause damage to systemic toxicity through prolonged or repeated exposure.
- Toxic to aquatic life with long lasting effects.

■Safety precautions

- Do not breathe dust/fume/gas/mist/ vapors/spray.
- Wash hands thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.

First-aid measures

IF SWALLOWED

Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair)

Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower

IF IN EYES

Rinse cautiously with water for several minutes. Remove contact lenses. if present and easy to do. Continue rinsing.

Immediately seek medical attention.

�HAK≪O

HAKKO CORPORATION

HEAD OFFICE 4-5, Shiokusa 2-chome, Naniwa-ku, Osaka 556-0024 JAPAN TEL: +81-6-6561-3225 FAX: +81-6-6561-8466 https://www.hakko.com E-mail: sales@hakko.com

OVERSEAS AFFILIATES

HONG KONG: HAKKO DEVELOPMENT CO., LTD.
TEL: 2811-5588 FAX: 2590-0217
https://www.haikko.com.cn E-mail: info@haikko.com.ch SINGAPORE: HAKKO PRODUCTS PTE, LTD.

Please access the web address below for other distributors https://www.hakko.com

© 2010-2024 HAKKO Corporation. All Rights Reserved.

Storage

Protect from sunlight. Store in a cool place.

Disposal

Dispose of contents/container in accordance with local and national regulations.

■Cautions for use

Refer to the SDS for details.