



FASTER THERMAL RECOVERY

Greater thermal capacity and rapid transmission to the tip means faster thermal recovery.

STABLE TEMPERATURE CONTROL

The temperature control sensor is built into the heating element for faster, more stable temperature control.

HIGH INSULATION

The highly insulated ceramic heating element never overheats. An insulation factor of over 100MΩ can be maintained even during actual use.

IMPROVED WORK EFFICIENCY

The compact, lightweight design with high cooling efficiency at the handle permits fatigue-free operation over long periods for maximum work efficiency.


SPECIFICATIONS

No.	924
Power Consumption	55W
Setting Temperature	300°C (572°F)
Insulation Resistance	Over 100MΩ
Total Length	210mm(8.2in.)
Weight	60g(0.13lb.)


REPLACEMENT TIP

*These Tips are optional.


Flat IC				
Part No.	Tip Size [mm (in.)]			
	A	B	C	D
924-T-1002	12.5 (0.5)	9.5 (0.37)	12.5 (0.5)	9.5 (0.37)
924-T-1003	15.5 (0.6)	12.5 (0.5)	15.5 (0.6)	12.5 (0.5)
924-T-1004	16.3 (0.64)	13.3 (0.52)	16.3 (0.64)	13.3 (0.52)
924-T-1005	17.0 (0.66)	14.0 (0.55)	17.0 (0.66)	14.0 (0.55)
924-T-1006	23.0 (0.9)	20.0 (0.78)	17.0 (0.66)	14.0 (0.55)
924-T-1007	20.0 (0.78)	17.0 (0.66)	20.0 (0.78)	17.0 (0.66)



Mini Flat IC		
Part No.	Tip Size [mm (in.)]	
	A	C
924-T-1010	6.0 (0.23)	5.0 (0.19)
924-T-1011	6.0 (0.23)	10.0 (0.39)
924-T-1012	7.0 (0.27)	12.5 (0.5)
924-T-1013	9.0 (0.35)	15.2 (0.6)
924-T-1014	9.0 (0.35)	18.0 (0.7)



Part No.	Supatula Type
924-T-1020	



⚠ CAUTION

Do not strike the soldering iron against the workbench or with any tool in order to remove excess solder from the tip. The ceramic heating element may be damaged if struck with excessive force.

中國RoHS: 產品中有毒有害物質或元素的名稱及含量

部件名稱	有毒有害物質或元素					
	鉛(Pb)	汞(Hg)	鎘(Cd)	六價鉻 [Cr(VI)]	多溴聯苯 (PBB)	多溴二苯醚 (PBDE)
螺帽	×	○	○	○	○	○
套頭	×	○	○	○	○	○
固定護套	×	○	○	○	○	○
電路版	×	○	○	○	○	○
插頭	×	○	○	○	○	○

○: 表示該有毒有害物質在該部件所有均質材料中的含量均在SJ/T 11363-2006標準規定的限量要求以下。
 ×: 表示該有毒有害物質至少在該部件的某一均質材料中的含量超出SJ/T 11363-2006標準規定的限量要求。

HAKKO HEATING TOOL