


HAKKO FG-460
FOOTWEAR TESTER


Footwear Tester for Individual Measurement & Evaluation of Electrical Resistance

NEW



■ Simple, yet user-friendly

Very easy-to-use footwear tester. Information of measurement and evaluation of electrical resistance at a glance. Meet the criteria of standards such as JIS T 8103:2010 and ANSI/ESD S20.20.



□ Individual measurement

Measure the anti-static performance of shoes individually. Prevents faulty measurement with the divider on test plate.



□ Evaluation external output

Evaluation results can be output through the external output terminal to interlock with other device, to open door, turn on signal, etc.



□ DIP switches for various settings

Upper and lower evaluation limits, evaluation buzzer, etc. can be made by setting the DIP switches.



FG-460

■ Packing list



Unit, Mounting base, AC adapter*, Test plate, Mounting screw (qty 2)**,
Pan head screw (qty 2), Wood screw (qty 2), Instruction manual

* AC adapter may not be included depending on the specifications.

** Delivered as they are screwed onto the unit.

NOTE: Stand (C5032) is sold separately.

■ Specifications

Rating	DC 24 V 33 mA	
Measurement voltage	DC 20 V	
Measurement range	Upper evaluation limit	1000 MΩ (1×10 ⁹ Ω)
		100 MΩ (1×10 ⁸ Ω)
		10 MΩ (1×10 ⁷ Ω)
	Lower evaluation limit	1 MΩ (1×10 ⁶ Ω)
Evaluation level accuracy		0.1 MΩ (1×10 ⁵ Ω)
	Conductivity evaluation	R < 0.1 MΩ (1×10 ⁵ Ω)
		R < 0.1 MΩ ± 5 %
	0.1 MΩ ≤ R ≤ 100 MΩ ± 10 %	
	100 MΩ < R ± 8 %	
Operating environment	Ambient temperature / humidity range 0 to 40°C, 20 to 90%RH (without condensation)	
Environment condition	Applicable rated pollution degree 2 (According to IEC / UL61010-1)	
Dimensions	120 (W) × 30 (H) × 185 (D) mm	
Weight*	0.55 kg	

■ Test plate

Cord length	1.6 m
Dimensions**	300 (W) × 30 (H) × 300 (D) mm
Weight**	1.9 kg

■ AC adapter

Output voltage	DC 24 V
----------------	---------

* Including mounting base

** Without cord

HAKKO
HAKKO CORPORATION
OVERSEAS AFFILIATES

U.S.A.
AMERICAN HAKKO PRODUCTS, INC.
28920 AVENUE WILLIAMS VALENCIA, CA 91355, U.S.A.
TEL: (661) 294-0090 FAX: (661) 294-0096
Toll Free (800)88-HAKKO
http://www.hakkousa.com

HONG KONG
HAKKO DEVELOPMENT CO., LTD.
ROOM 1504, EASTERN HARBOUR CENTRE,
28 HOI CHAK STREET, QUARRY BAY, HONG KONG.
TEL: 2811-5588 FAX: 2590-0217
http://www.hakko.com.hk
E-mail:info@hakko.com.hk

SINGAPORE
HAKKO PRODUCTS PTE LTD
1, GENTING LINK #02-04
PERFECT ONE, SINGAPORE 349518
TEL: 6748-2277 FAX: 6744-0033
http://www.hakko.com.sg
E-mail:sales@hakko.com.sg

CA00480QbYa002 2017.9

Please access to the following for the other sales affiliates and distributors.
<http://www.hakko.com>

Specifications and design are subject to change without notice. Copyright HAKKO Corporation. All right reserved.